

THE WIDE RANGE OF UV - IR TECHNOLOGY



UV-Meter Silver Line Series

- + UV intensity mW/cm^2
- + 2 channel x1/x10
- + auto off



The UV-Meter Silver Line is a high quality UV measuring instrument.

It is used for the measurement of the intensity of UV light.

All measurements are expressed in mW/cm^2 in order to compare light sources or to check uniformity of the light emission.

Typical application fields are the control of units for the exposure of diazo, polymer, chromaline and daylight films in the graphic arts industry, suntan equipment, sterilisation units and other fields of photo biology.

Special feature:

In order to save battery energy, the UV-Meter Silver Line will turn off automatically after one minute.

The UV-Meter Silver Line is available in five different measuring ranges:
(Please state upon order)

- 6.2.1. UV-Meter Silver Line UV-V (Diazo) 350 – 460 nm
- 6.2.2. UV-Meter Silver Line UV-A 315 – 400 nm
- 6.2.3. UV-Meter Silver Line UV-B 280 – 315 nm
- 6.2.4. UV-Meter Silver Line UV-C 230 – 280 nm
- 6.2.5. UV-Meter Silver Line Full UV 230 – 410 nm

The display readings are fictitiously. The basic setting is done by means of a potentiometer.

Technical Data:

Max. Power input :	sensor input $1000W/cm^2$
Wavelength:	315 – 410 nm UV-A (or other)
Temperature:	0 - 45 C
Display:	4 Digits
Range X 1 :	0 - 19,99 mW/cm^2
Range X 10 :	0 - 19 9,9 mW/cm^2
Weight:	approx. 200 grams
Battery:	2 x 3.6 Volt Lithium Battery
Dimensions:	140 mm x 70 mm x 13 mm
Sensor cable:	1 meter
Sensor Ø	40 mm x 10 mm
Base Accuracy:	$\pm 5 \%$

The probe-type sensor of the UV-Meter can withstand max. $110^\circ C$ for up to 10 seconds. The temperature of the housing should not exceed 45° Centigrade.

Calibration:

In order to keep its full function and precision it is recommended to have re-calibration done once per year. Re-calibration will also be necessary after change of battery. PTB traceable calibration

Subject to change without prior notice © 2006-09